


cameras.

For Security Vari-Focal



YV2.8×2.8SA-2





• Designed to maximize optical performance with high-accuracy

aspheric lens, low-dispersion glass, and high refractive-index glass.





VARI














 High image-quality monitoring with optical performance supporting 3 megapixels. WIDE 2.8mm, achieving a horizontal field angle of 100 degrees 14.8 (when used on 1/3 cameras). • Compact and lightweight design, best suited for use with dome



Unit: mm

Focal Length (mm)			2.8~8 (2.8×)
Iris Range			F1.2 ∼ Close
Operation	Zoom		Manual
	Focus		Manual
	Iris		Manual
Angle Of View (H×V)	1/3"	WIDE	100°00′ × 73°45′
		TELE	35°03′ × 26°18′
	1/4"	WIDE	73°45′ × 54°49′
		TELE	26°18′ × 19°44′
Focusing Range (From Front Of The Lens) (m)			∞ ~ 0.3
Object Dimensions at M.O.D. (HXV) (mm)	1/3"	WIDE	744 × 468
	1/3	TELE	197 × 146
	1/4"	WIDE	468 × 323
		TELE	146 × 108
Back Focal Distance (in air) (mm)			7.70
Exit Pupil Position (From Image Plane) (mm)			314
Filter Thread (mm)			_
Mount			CS
Mass (g)			50
Remarks			With Metal Mount





