

WAT-221S2 1/2" Multi-function & High Sensitivity Camera


Advanced setting for general surveillance, embedded system and research study



Key features

- 1/2-inch CCD sensor with high sensitivity
- Min. illumination 0.006 lx F1.2 (AGC HIGH=44dB, shutter=OFF, NR=ON)
- 3DNR, wide dynamic range, HSBLC (Highlight Suppression Back Light Compensation)
- White blemish correction, slow-shutter, privacy masking and RS-485 (Pelco-D) compatible
- OSD (On Screen Display) – Easy installation through a remote controller provided in kit

Dimensions



Specifications

Video standard		PAL
Pick-up element		1/2 inch interline transfer CCD image sensor
Number of effective pixels		752(H) × 582(V)
Unit cell size		8.6μm(H) × 8.3μm(V)
Imaging system		Ye, Cy, Mg, and G complementary color mosaic filters on chip
Synchronizing system		Internal
Scanning system		2:1 interlace
Video outputs		Composite: 1.0 V(p-p) 75Ω (Unbalanced)
		Y/C OUT : Y: 1.0V(p-p), C: 0.3V(p-p) 75Ω
Resolution (H)		More than 550TVL (Center)
Minimum illumination		0.006 lx F1.2 (AGC HIGH=44dB, Shutter=OFF, NR=ON)
		0.0004 lx F1.2 (AGC HIGH=44dB, Shutter=x16, NR=ON)
S/N		More than 55dB (AGC OFF=-3dB, γ=1.0)
Function settings		OSD : Remote controller, RS-485 (Pelco-D), Communication : RS-485 (Pelco-D)
AE mode	Fixed	x2, x4, x8, x16, x32, x64, x128, x256 (field)
		1/50, 1/120 sec.
		1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/10000 sec.
	EI	1/50 - 1/100000 sec.
		x16 - 1/100000 sec.
White balance		ATW, AWB, ACR, PWB, PRESET (3200K, 4300K, 5100K, 6300K)
AGC	ON	-3 - 32dB (LOW), -3 - 44dB (HIGH)
	OFF	-3dB
MGC		-3 - 44dB (1dB step)
Day/Night		—
Gamma characteristics		γ≒0.35, 0.4, 0.45, 0.5, 0.55, 0.6, 0.7, 0.8, 1.0
Video level		Adjustable
Noise reduction		3DNR OFF/ON Level adjustable
Wide dynamic range		D-WDR OFF/ON Level adjustable
Lens iris		Video / DC (EIAJ, Auto-select)
Back light compensation		BLC, HSBLC
White blemish correction		Up to 64 pixels
Sharpness		Level adjustable
Defog		OFF/ON Level adjustable
Digital zoom		ZOOM (x2 - x256), PAN/TILT
Privacy mask		4 masks
Mirror image		OFF, V-FLIP, H-FLIP, HV-FLIP
Freeze		—
Motion detection		OFF/ON Select from 96 detection areas
Neg.image		—
Interface		BNC (Composite Video), Y/C OUT, Power in, Remote control (RC-01), REMOTE (Alarm, RS-485)
Power supply		DC+12V±10%
Power consumption		1.32W (110mA)
Operating temperature		-10 - +50℃
Storage temperature		-30 - +70℃
Operating / Storage humidity		95% RH or less (Without condensation)
Lens mount		CS mount
Weight		Approx. 150g
Accessories		WPDC12 (DC plug), Hex, wrench, RC-01 (Remote controller), I/O cable

