

WAT-230V2 (P3.7) 1/4" Miniature Camera


Ultra-compact design for easy installation and limited space



Key features

- Wide input voltage range (*DC 5V to 12V)
 - Advanced setting available by OSD (On Screen Display) through an optional remote control
- ※Glass lenses and pinhole lens are not interchangeable

Dimensions



Specifications

		NTSC	PAL
Video standard		1/4 inch interline transfer CCD image sensor	
Pick-up element		1/4 inch interline transfer CCD image sensor	
Number of effective pixels		976(H) × 494(V)	976(H) × 582(V)
Unit cell size		3.75μm(H) × 5.56μm(V)	3.75μm(H) × 4.69μm(V)
Imaging system		Ye, Cy, Mg, and G complementary color mosaic filters on chip	
Synchronizing system		Internal	
Scanning system		2:1 interlace	
Video outputs		Composite: 1.0 V(p-p) 75Ω (Unbalanced)	
Resolution (H)		More than 650TVL (Center)	
Minimum illumination		0.6 lx F4.5 (AGC ON=45dB, Shutter=OFF)	
S/N		More than 50dB (AGC OFF=0dB, γ≈0.45)	
Function settings		OSD : Remote controller	
AE mode	Fixed	1/60, 1/100 sec.	1/50, 1/120 sec.
		1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/10000 sec.	
	EI	1/60 - 1/100000 sec.	1/50 - 1/100000 sec.
White balance		ATW, AWB, ACR, PWB, MWB, PRESET (5100K, 6300K)	
AGC	ON	0 - 45dB	
	OFF	0dB	
MGC		0 - 42dB (6dB step)	
Day/Night		Digital Auto, Manual	
Gamma characteristics		γ≈0.45	
Video level		Adjustable	
Noise reduction		2DNR OFF/ON Level adjustable	
Wide dynamic range		D-WDR OFF/ON Level adjustable	
Lens iris		—	
Back light compensation		BLC, HSBL	
White blemish correction		Up to 64 pixels	
Sharpness		Level adjustable	
Defog		OFF/ON Level adjustable	
Digital zoom		—	
Privacy mask		8 masks	
Mirror image		OFF, H-FLIP	
Freeze		—	
Motion detection		—	
Neg.image		—	
Interface		4P connector (Composite Video, Power in), Remote control (RC-01)	
Power supply		DC+5V ~ 12V	
Power consumption		0.775W/155mA (DC+5V), 0.78W/65mA (DC+12V)	
Operating temperature		-10 - +50°C	
Storage temperature		-30 - +70°C	
Operating / Storage humidity		95% RH or less (Without condensation)	
Lens mount		M13 P=1.0	
Standard lens		3745B-13P (f3.7 F4.5)	
Weight		Approx. 27g	
Accessories		4P cable	

